

IP Pro IPRW

Wiegand Reader Series



The SDC IPRW Series is the perfect companion for our IP Pro Controller. It provides 26-bit Wiegand output while being HID proximity compatible. Use as Entry or Exit Reader with the IP Pro System



MODELS

IPRW300 IP Pro Mini Wiegand Reader, Mullion Mount, includes black and white snap-on cover
- supports HID Proximity (125 kHz)

IPRW500 IP Pro Wiegand Reader, U.S. Single Gang mount, includes black and white snap-on cover
- supports HID Proximity (125 kHz)



ACCESSORIES

PROX CARDS AND KEY FOBS



HID1326-25 Proximity Card , 25 Cards



HID1326-100 Proximity Card, 100 Cards



HID1346-10 Proximity Key Fob, 10 Key Fobs

HID1346-100 Proximity Key Fob, 100 Key Fobs



PTAG-10

Adhesive Proximity Disc Tag, 10 Tags

PTAG-25

Adhesive Proximity Disc Tag, 25 Tags





SPECIFICATIONS IPRW300

Operating Voltage	5-16 VDC
Current Consumption	30mA typical, 75mA peak
Housing	Indoor/Outdoor (IP67) w/potted electronics
Temperature	-40°F to + 149°F
Dimensions	3.2"H x 1.7"W x .7"D
Output	26-bit Wiegand
HID-compatible	125Khz RFID
Max. Cable Distance to Host	328ft @ 12VDC, 100ft @ 5VDC
Read Range	up to 5" (126 mm)

SPECIFICATIONS IPRW500

Operating Voltage	5-16 VDC
Current Consumption	35mA typical, 75mA peak
Housing	Indoor/Outdoor (IP67) w/potted electronics
Temperature	-40°F to + 149°F
Dimensions	4.6"H x 3"W x .4"D
Output	26-bit Wiegand
HID-compatible	125Khz RFID
Max. Cable Distance to Host	328ft @ 12VDC, 100ft @ 5VDC
Read Range	up to 8" (202 mm)