

NEW 4G / VoLTE Cellular Select Gate with free AT&T SIM Card ready for Activation



SGMC MOBILE APP

Available on the App Store and Google Play
For use with Entire Select Gate Series Product Line

See Mobile App Information for Specifics



STANDARD FEATURES

- ◆ Gate Control via SMS (Short Message Service) Text, **Select Gate Mobile Control** App, Keypad, Remote Touch Tones, Card Readers or Transmitters (Optional)
- ◆ 10 Phone Number Capacity (dialed via keypad)
- ◆ 1000 Caller ID Recognizable Phone Numbers
- ◆ Call Forward to 3 Rollover Phone Numbers in the users Programmed Sequence
- ◆ 2000 Mix & Match Pins / Transmitters / Cards
- ◆ Pin Code Range from 0001 to 9999
- ◆ Card Number Range from 00001 to 65534
- ◆ Site Code Range from 001 to 255
- ◆ Overhead LED lights for easy viewing at night
- ◆ Blue back lit keypad for the ease of reading
- ◆ Latch Open Gate via SMS Text, Mobile App or Remote Touch Tones
- ◆ Hold Gate Open 1 Hour via SMS Text, Mobile App or Remote Touch Tones
- ◆ Built-in 26 Bit Wiegand Input for Card Access
- ◆ REX (Request to exit) Input
- ◆ Gate Position Sense Input
- ◆ Signal Strength verifier via SMS Text
- ◆ Optional Plug-in RF Receiver for use with any SES SelectPass Transmitters. (Model: SG3DMRCL)
- ◆ Auxiliary Relay for triggering an external camera (or other device) when the call button is pressed or a PIN / Card is Used

SPECIFICATIONS

- ◆ **Mounting dimensions:**
SG3DMCL 7" H x 10" W x 6" D
- ◆ **Construction:**
Back box: .090 aluminum, primed and painted black texture for exterior use.
Face plate: stainless steel
- ◆ **Power Input:**
12-24V AC/DC (16.5V 20VA AC Transformer Included)
- ◆ **Current Draw:**
90mA @ 12VDC; 80mA @ 24VDC
- ◆ **Operating Environment:**
Temperature -20 F to +140 F, Relative Humidity 5% to 95% non-condensing.
- ◆ **Relay Output (2):**
Form C dry contact, 24 V @ 3 AMPS.
- ◆ **Mounting:** Surface or Pedestal.
- ◆ **Memory Type:** non-volatile.
- ◆ **Tone Detection:**
Crystal controlled capable of detecting 100 mS. DTMF tone, (detects touch tones only).
- ◆ **Shipping Weight:**
Approx. 15 lbs. for SG3DMCL only, actual shipping weight dependent on final system configuration.

SG3DMCL compatible with AT&T, and other GSM carriers SIM Cards, if uncertain which network you are using please check with your service provider; Good mobile GSM coverage with high signal strength is recommended for trouble free installation. SGMC Mobile App can be used with any carrier.

NEW 4G / VoLTE Cellular Select Gate with free AT&T SIM Card ready for Activation



SGMC MOBILE APP

Available on the App Store and Google Play
For use with Entire Select Gate Series Product Line

See Mobile App Information for Specifics



STANDARD FEATURES

- ◆ Gate Control via SMS (Short Message Service) Text, **S**elect **G**ate **M**obile **C**ontrol App, Keypad, Remote Touch Tones, Card Readers or Transmitters (Optional)
- ◆ 10 Phone Number Capacity (dialed via keypad)
- ◆ 1000 Caller ID Recognizable Phone Numbers
- ◆ Call Forward to 3 Rollover Phone Numbers in the users Programmed Sequence
- ◆ 2000 Mix & Match Pins / Transmitters / Cards
- ◆ Pin Code Range from 0001 to 9999
- ◆ Card Number Range from 00001 to 65534
- ◆ Site Code Range from 001 to 255
- ◆ LED lights for easy viewing at night
- ◆ Blue back lit keypad for the ease of reading
- ◆ Latch Open Gate via SMS Text, Mobile App or Remote Touch Tones
- ◆ Hold Gate Open 1 Hour via SMS Text, Mobile App or Remote Touch Tones
- ◆ Built-in 26 Bit Wiegand Input for Card Access
- ◆ REX (Request to exit) Input
- ◆ Gate Position Sense Input
- ◆ Signal Strength verifier via SMS Text
- ◆ Auxiliary Relay for triggering an external camera (or other device) when the call button is pressed or a PIN / Card is Used

SPECIFICATIONS

- ◆ **Mounting dimensions:**
SG2CL 7" H x 9 7/16" W x 4 9/16" D
- ◆ **Construction:**
Back box: .090 aluminum, primed and painted black texture for exterior use.
Face plate: stainless steel
- ◆ **Power Input:**
12-24V AC/DC (16.5V 20VA AC Transformer Included)
- ◆ **Current Draw:**
90mA @ 12VDC; 80mA @ 24VDC
- ◆ **Operating Environment:**
Temperature -20 F to +140 F, Relative Humidity 5% to 95% non-condensing.
- ◆ **Relay Output (2):**
Form C dry contact, 24 V @ 3 AMPS.
- ◆ **Mounting:** Surface or Pedestal.
- ◆ **Memory Type:** non-volatile.
- ◆ **Tone Detection:**
Crystal controlled capable of detecting 100 mS. DTMF tone, (detects touch tones only).
- ◆ **Shipping Weight:**
Approx. 15 lbs. for SG2CL only, actual shipping weight dependent on final system configuration.

SG3DMCL compatible with AT&T and other GSM carriers SIM Cards, if uncertain which network you are using please check with your service provider; Good mobile GSM coverage with high signal strength is recommended for trouble free installation. SGMC Mobile App can be used with any carrier.