

HiB68

3.6mm fixed lens, dark gray housing



Features

- Next generation of Intensifier® technology provides an even more vivid color image in low light situations
- Preset image modes offer convenient settings for different environments
- Supports up to full HD 1080p resolution @ 30fps
- Built-in temperature and humidity sensor control automatic heater operation
- True WDR (wide dynamic range) operation
- IP68 compliant, weather resistant
- Junction box included for convenience
- 5 year warranty



Included Junction Box



Camera Specifications

Image Sensor	Progressive scan 1/2.8" Sony STARVIS CMOS Sensor, 2MP
Maximum Resolution	1920x1080
Field of View	89° Horizontal, 47° Vertical
Minimum Illumination	0.001 lux
White Balance	Auto/AWB/AWB - SET/Manual
Compensation	WDR
Day/Night	Auto/Color/B&W
DNR	Off/Low/Middle/High
Output	TVI
S/N Ratio	More than 50dB (AGC OFF/ Weight ON)

Video Specifications

Main Resolution	1920x1080 / 1280x720 @ 30fps
Privacy Mask	ON/OFF 16 zones
Motion	ON/OFF 4 zones
Negative Image	ON/OFF
Mirror/Flip	ON/OFF
Shutter	Auto/Manual/Flicker
Intensifier®	Auto/OFF (selectable limit x2 ~ x32)
Backlight	OFF/HLC/BLC/WDR
AGC (Auto Gain Control)	0 ~ 10 (level adjustable)
Sharpness	0 ~ 10 (level adjustable)
WDR	Normal/ROI
Defog	ON/OFF

Operating & Unit Specifications

Power	12VDC (power supply not included)
Power Consumption	200mA±10%(12VDC)
Operating Temperature	-40°F to 140°F
Operating Humidity	0% - 90% relative humidity
Unit Dimensions	3"(Φ) x 7.3" (H)
Unit Weight	1.2 lbs

Optional Accessories



PSW5
12VDC
Power Supply



TVIUTPPT
HD Video
Transceiver with
Pigtail (Balun)



TVIUTP
HD Video
Transceiver