

5MP IP Dome Camera with Advanced Analytics, NDAA Compliant

O5D2

2.8mm fixed lens, white housing















Features

- \bullet Supports up to 5MP @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- H.265/H.264/MJPEG compression supported
- True Day/Night operation (IR cut filter)
- Adaptive IR LEDs reduce IR saturation
- IR range: Up to 100' (depending on scene reflection)
- Cloud recording and playback support*
- Face/Human/Vehicle/Scene Change Detection**
- Micro SD slot up to 256GB (card not included)

- True WDR (wide dynamic range) operation
- IP67 compliant, weather resistant
- IK10 compliant, vandal resistant
- Junction box included (works with NPT/BSP specifications)
- Conformant with ONVIF Profile T
- 5 year warranty
- NDAA Compliant***



Camera Specifications		
Image Sensor	Progressive scan 1/2.7" CMOS, 5MP	
Maximum Resolution	2592 x 1944	
Field of View	98.5° (H) 82.1° (V) 110.9° (D)	
Minimum Illumination	0.02 lux @ F1.6, AGC ON, 0 lux (IR LED on)	
Day/Night	Smart IR	
White Balance	Auto, Indoor, Outdoor, Manual	
Compensation	True WDR (120dB), BLC, HLC	
Electronic Shutter Speed	1 - 1/100000 sec.	
DNR	3D DNR	

Video Specifications		
Main Resolution	2592x1944/ 2560x1440 / 2304x1296 / 1980x1080 / 1280x720 @ 30fps	
Compression	H.265, H.264 (HP/MP/BP), MJPEG	
Video Settings	Region of Interest, Privacy masking, Brightness, Contrast, Hue, Saturation, Denoise, Antiflicker, Day/Night mode, Infrared settings, Exposure, Gain, Corridor Pattern, Image flip/mirror	
Bitrate Control	VBR, CBR (64Kbps ~ 8Mbps)	
Multiple Streaming	3 streams	

Network Specifications		
Protocols	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, $802.1x$, UPnP, HTTP, HTTPS	
DDNS support	Speco DDNS (free of charge)	
Security	User ID & Password protection, IP/Mac address filtering, digest authentication	
User Access	Max. 10 simultaneous users, Actual number of users may vary depending on bandwidth	
Client Specifications		
Chem opecinications		

Client Specifications	
Web Browser Support	Windows (Internet Explorer 8 and up)
PC Application	SecureGuard® VMS, SecureGuard® CMS
Mobile	SecureGuard [®] Client, Speco Blue (iPhone [®] and Android [™])
Other Platforms	Apple TV, Amazon Fire TV

Audio Specifications	
Audio Codec	G.711 A / G.711 U
Interfaces	
Ethernet	10/100 Mbps
Power	DC jack
Microphone Input	Built-in mic and Mono 3.5mm input
Audio Output	No
Card Slot	MicroSD, up to 256GB (not included)
Alarm	1CH alarm input; 1CH alarm output
Reset	Yes

System Specifications		
PoE	Standard (IEEE 802.3af)	
Analytics	Motion, missing object, abandoned object, intrusion, vehicle, human, tampering, scene change, and face detection	
Alarm Triggers	Analytics, SD card error	
Alarm Events	FTP upload, email upload	
Image Settings	Watermark, IP address filtering, video mask, password protection	

Power	PoE, 12VDC (power supply not included)
Power Consumption	< 6.0W
Operating Temperature	-40°F ~ 140°F
Operating Humidity	Less than 95 % (non-condensing)
Unit Dimensions	4.7" (φ) x 3.5" (H)
Unit Weight	1.43 lb.
Certifications	FCC, RoHS

- *with Speco Cloud subscription service
- with compatible Speco recorde
- ***Products are in compliance with NDAA Section 889 Part B Guidelines

Operating & Unit Specifications





Optional Accessories



PoE Injector



Power Supply



CMT1





CLTX1 Ceiling Mount

4" Extension



O5VLWMJ Wall Mount



CLT2J Ceiling Mount

Cameras Interfaces













ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 11/15/22













