

Four Zone 160 Watt Commercial Amplifier

PL200M 160W commercial amplifier

Features

- Simultaneous playback of up to 5 sources into up to 4 zones.
- 4 sets of 4/8 Ohms or 70/25V outputs
- Telephone paging interface, and limited music on hold functionality via a monitor output
- Mic1 selectable priority paging with internal toggle
- Energy saving intelligent cooling fan
- Separate controls (gain, bass, treble volume) and mute for each source
- Separate volume control and LED power indicator for each zone
- Rack-mount design with built-in handles (3U)
- 3 combination XLR/ 1/4" inputs with selectable phantom power, line level or mic level



Specifications

RMS Output Power	40W (Per zone for 160W total)
Max. Output Power	90W (Per zone for 360W total)
AC Power Consumption	400W (total)
Power Supply	AC 115V/230V, 60/50Hz
Zones	4
Speaker Outputs	4/8 Ohms, 70/25V (per zone)
Other Outputs	Aux (Terminal) (per zone)
Inputs	3 x Mic/Aux inputs (Combo XLR/ 1/4"), 2 x Aux (Stereo RCA), 1 x TEL (Terminal)
Frequency Response	50Hz ~ 17KHz (±3dB)
Tone Control	Bass ± 10dB, Treble ± 10dB
THD	Less than 0.5% @ 1KHz
Signal/Noise Ratio	Microphone: >55dB, Line: >60dB
Controls	Volume for each source, Volume for each zone, Volume for monitor, Volume for headphone, Zone selector for each source, Monitor selector for each zone, Input type selector
Telephone	TEL in
Indicators	Power, power level
Dimensions	19" (W) x 5.2" (H) x 12.2" (D)
Weight	33.3 Lbs.
Listings	CE, FCC, RoHS

NDA A
COMPLIANT

*Products are in compliance with NDA A Section 889 Part B Guidelines

Speco Technologies is constantly developing and improving products.
We reserve the right to modify product design and specifications without notice
and without incurring any obligation. Spec Rev. 2/24/22