

NEXUS™ UL® Contractor Series 70V Commercial Metal Back Can Speakers

SP5NXCTUL 5.25" speaker, white housing

SP6NXCTUL 6.5" speaker, white housing

Features

- Easy select transformer dial
- Fire retardant metal backcan
- Safety loop for additional mounting security
- Ported bass
- Quick-snap connection terminals
- Includes mounting brackets



Specifications

	SP5NXCTUL	SP6NXCTUL
RMS Power	40W	60W
Max. Power.....	80W	120W
Transformer Type	70V	70V
Transformer Power Taps	10W, 5W, 2.5W 0.625W & 8 Ohms	30W, 15W, 7.5W, 3.7W 1.9W & 8 Ohms
Termination Type	Phoenix Connector	Phoenix Connector
Sensitivity (1W/1M).....	88dB	87dB
Maximum SPL (Pmax/1M).....	96dB	97dB
Driver Impedance	8 Ohms	8 Ohms
Magnet.....	12 oz. ferrite	12 oz. ferrite
Frequency Response Range.....	75Hz ~ 20kHz	60Hz ~ 20kHz
Dispersion @ 1000Hz	110° conical	110° conical
Driver	5.25" polypropylene woofer, 0.75" silk tweeter	6.5" polypropylene woofer, 0.75" silk tweeter
Speaker Dimensions	9.25" (Dia.) x 7.25" (D)	10.25" (Dia.) x 7.75" (D)
Mounting Dimensions.....	7.8" (Dia.)	8.75" (Dia.)
Minimum Mounting Depth.....	7"	7.5"
Weight	7.2 lbs.	9.8 lbs.
Material.....	Baffle: Fire-resistant ABS Backcan: Heavy guage plated steel Grille: Steel	Baffle: Fire-resistant ABS Backcan: Heavy guage plated steel Grille: Steel
Color	White	White
UL Rating.....	UL1480	UL1480 and UL2043

NDAA
COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines

Speco Technologies is constantly developing and improving products.
We reserve the right to modify product design and specifications without notice
and without incurring any obligation. Spec Rev. 3/11/22