



# HID LITEBOX® RECHARGEABLE LANTERN



- Material/Lens** High-impact ABS thermoplastic housing. Rubberized impact bumper, lens ring and cushioned-grip handle. Glass lens
- Dims/Weight** Length: 14.9 in. (38 cm); Body Width: 5.1 in. (13 cm); Overall Height: 8.8 in. (23 cm); Head Diameter: 7.7 in. (20 cm); Weight: 10.1 lbs (4.6 kg)
- Light Source** 35W High Intensity Discharge xenon lamp w/ 2000 hr minimum lifetime. Deep-dish parabolic reflector produces a long range high intensity beam with optimum peripheral illumination for scene lighting
- Output/Runtime** 3,350 lumens; 1,000,000 candela; runs 1.75 hours
- Switch** Toggle switch
- Battery** Zero -maintenance 12V, 7.2Ah sealed lead acid battery
- Features** - 90° swivel neck allows you to aim the beam where you need it for optimum task lighting  
- Serialized for positive identification
- Models** Standard System - International safety orange or black; includes shoulder strap; AC and DC chargers and charge rack; includes 10ft (3 meter) 12V DC power cord and flood lens. Ideal for field maintenance, inspection of construction sites, and remote equipment.  
Vehicle Mount System - International safety orange; includes vehicle-mountable hard-wire rack, 10ft (3 meter) 12V DC power cord, shoulder carrying strap and flood lens
- Approvals** Most models meet applicable European Community Directives.  
Rack meets requirements of NFPA 1901-14.1.10.2 (2016) mounted in any position
- Warranty** Streamlight warrants this product to be free of defects for a lifetime of use except for batteries and bulbs, abuse and normal wear. We will repair, replace or refund the purchase price of this product should we determine it to be defective. This limited lifetime warranty also excludes rechargeable batteries, chargers, switches and electronics which have a 2 year warranty with proof of purchase. **THIS IS THE ONLY WARRANTY, EXPRESSED OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. INCIDENTAL, CONSEQUENTIAL OR SPECIAL DAMAGES ARE EXPRESSLY DISCLAIMED EXCEPT WHERE SUCH LIMITATION IS PROHIBITED BY LAW.** You may have other specific legal rights which vary by jurisdiction.

Description	UPC	Item #
HID LiteBox Standard System - 230V AC/12V DC - Orange	080926-45602-0	45602
HID LiteBox Standard System - 240V AC/12V DC - Orange	080926-45603-7	45603
HID LiteBox Standard System - 120V/100V AC/12V DC - Orange	080926-45601-3	45601
HID LiteBox Standard System - 120V/100V AC/12V DC - Black	080926-45621-1	45621
HID LiteBox Vehicle Mount System - 12V DC direct wire rack - Orange	080926-45605-1	45605
HID LiteBox (WITHOUT CHARGER) - Orange	080926-45600-6	45600
HID LiteBox (WITHOUT CHARGER) - Black	080926-45620-4	45620

Assembled in USA

	Description	UPC	Item #
	DC2 direct wire charge cord	080926-22050-8	22050
	DC1 Charge Cord	080926-22051-5	22051
	12V DC power cord 10ft (3 meters)	080926-22056-0	22056
	120V/100V Charge Cord - HID LiteBox, E-Flood LiteBox HL	080926-22085-0	22085
	230V Charge Cord - HID LiteBox, E-Flood LiteBox HL	080926-22061-4	22061
	240V [UK] Charge Cord - HID LiteBox, E-Flood LiteBox HL	080926-22062-1	22062
	240V [AUS/NZ] Charge Cord - HID LiteBox, E-Flood LiteBox HL	080926-22048-5	22048
	Locking Device (keyed differently) *Must be factory installed	080926-40163-1	40163
	Quick Release Strap	080926-44050-0	44050
	Shoulder Strap	080926-45232-9	45232
	Standard System Mounting Rack Orange	080926-45070-7	45070
	Direct Wire 12V DC Mounting Rack** Orange	080926-45071-4	45071
	Standard System Mounting Rack** Black	080926-45075-2	45075
	Direct Wire 12V DC Mounting Rack Black	080926-45071-4	45076
	Battery - HID LiteBox/E-Flood LiteBox HL	080926-45630-3	45630
	HID Bulb Kit	080926-45637-2	45637
	HID lens/reflector assembly**	080926-45638-9	45638
	HID IR Filter	080926-45654-9	45654
	HID Flood Lens	080926-45657-0	45657