

NEW



SLIDE GATE OPERATOR

2200_{LBS} CAPACITY



RESIDENTIAL AND COMMERCIAL
CLASS I, CLASS II, CLASS III, AND CLASS IV VEHICULAR GATE OPERATOR

New "VFLEX" Control Board

Multi-Layer Corrosion Protection
 • G90 Galvanized
 • Clear Zinc Plating
 • UV Rated Powder coating

New Redesigned Chassis
 Post Mount Ready

Integrated Modular Power Box
 • Convenient Fuse Access
 • LED Status Indicators
 • Convenient Power Switch
 • E-Z Access Power Outlet
 • E-Z Set-up 115V/230V
 • (Optional) Low Voltage
 Removable Power Supply

Built-In Heater
 • Cold Weather Operation
 Down to -20°F

Conveniently Located Manual
 Release and Reset Switches

Convenient J-Box for
 High Voltage Wiring



COMPATIBLE WITH VIKING WIRELESS PRODUCTS

- Wireless Master/Slave Kit provides secure and reliable wireless communication.
- Remote access to the control board settings, programming, operator diagnostics, controls, gate status and error notifications, all from the convenience of a computer or any compatible handheld device.
- Plug & Play connection for Viking wireless expansion products.



BATTERY BACKUP

- Standard Battery Backup provides 100 continuous cycles at 100% duty cycle.
- With Viking's "True" Battery Backup System, batteries are not used during normal operation, maximizing battery life.



LIGHTNING PROTECTION

- Advanced Lightning strike protection up 20,000 volts / 10,000 Amps.
- On-board surge protection monitoring.



DIGITAL LIMITS

- Simple, push button limit setup.
- Adaptive Digital Limit control maintains open and close limit position during changing environments and power failures.



DIAGNOSTICS DISPLAY

- On-board LCD screen displays voltages, amps, gate status and diagnostics.



INTERGATED HEATER

- Built-in heater for operating temperatures down to -20°F.
- This will allow you run your operator in the coldest conditions.



SOLAR SMART

- Power Saving technology minimizes current draw while at standby.



Operational Voltage	... 24 VDC with 1HP Motor
Main Power Source Options	... 115 / 230 VAC Single Phase 24V AC/DC (Included Power Supply)
Battery	.. 7 AmpHr 12VDC x 2
Max Gate Capacity	... 2200 lbs / 75'
Operating Speed	... 12" per second
Battery Backup	... 100 Full Cycles (2200 lbs)
Maximum Duty Cycle	... 100% Continuous Cycle
Operating Temperature	... - 20° F to + 158° F

WARRANTY:

**7 YEAR RESIDENTIAL
 5 YEAR COMMERCIAL**

