











Standard trims

	EO	TP	DT	K	L	T
						
	Exit only	Key locks thumbpiece	Pull when dogged	Key locks knob	Key locks lever #06 Standard	Key locks thumbturn (Pull required)
Product description	8827EO	8827TP ^{1,2}	8827DT	8827K ^{1,2,3}	8827L ^{1,2,4,5,6}	8827TL ^{1,5,6}
Trim description	—	880TP-V	880DT-V	880K-V	373L	377T x 880DT-V
Escutcheon plate size	—	3" x 14 ³ / ₁₆ " x ³ / ₃₂ "	3" x 14 ³ / ₁₆ " x ³ / ₃₂ "	3" x 14 ³ / ₁₆ " x ³ / ₃₂ "	11 ¹ / ₁₆ " x 7 ¹ / ₂ " x ⁷ / ₈ "	11 ¹ / ₁₆ " x 7 ¹ / ₂ " x ⁷ / ₈ "
Grip mounting center	—	5 ¹ / ₂ "	5 ¹ / ₂ "	—	—	—
Projection	—	2"	2"	2 ³ / ₄ "	2 ⁵ / ₈ "	1 ¹³ / ₁₆ "
ANSI function	01	05	02	08	08/09	11/12
Cylinder type	—	Rim	—	Rim	1 ¹ / ₂ " Mortise	1 ¹ / ₂ " Mortise
Sex bolt quantity #425 (optional)	16	12	12	12	12	12

Optional trims

	TP	DT	K	EO
				
	Key locks thumbpiece	Dummy trim Pull when dogged	Key locks knob	Exit only
Product description	8827TP x 608TP ^{1,3}	8827DT x 608DT	8827K x 606K ^{1,3}	8827L x 880EO
Trim description	608TP-V	608DT-V	606K-V	880EO-V
Escutcheon plate size	1 ⁵ / ₈ " x 13 ¹ / ₂ " x ³ / ₁₆ "	1 ⁵ / ₈ " x 13 ¹ / ₂ " x ³ / ₁₆ "	1 ⁵ / ₈ " x 8 ³ / ₄ " x ³ / ₁₆ "	3" x 14 ³ / ₁₆ " x ³ / ₃₂ "
Grip mounting center	5 ¹ / ₂ "	5 ¹ / ₂ "	—	—
Projection	2 ¹ / ₆ "	2 ¹ / ₆ "	2 ³ / ₄ "	—
ANSI function	03	02	08	01
Cylinder type	Rim	—	Rim	—
Sex bolt quantity #425 (optional)	NR	NR	NR	12

¹ If no cylinder operation is required, specify "BE" blank escutcheon, trim always operable; example 8827TP-BE.

² Matching dummy trim available, use suffix "DT"; example 8827K-DT.

³ Can be furnished with NL action, thumbpiece or knob operates only when key is used. Use suffix NL; example 8827TP-NL.

⁴ When using sex bolts, an 889 cover plate is required. See page 24.

⁵ When using on wood doors without sex bolts, "WDA" cover plate is required. See page 24.

⁶ The 373L and 377T are shipped L or TL. An NL cylinder plate is also furnished standard (for operation only when key is used).

NR-Not recommended

Notes