

Standard trims

	EO	NL	TP	DT	K	L
	Exit only	<b>Night latch</b> Key retracts latchbolt	Key locks thumbpiece	<b>Dummy trim</b> Pull when dogged	Key locks knob	<b>Key locks lever</b> #06 Standard
<b>Product description</b>	88EO	88NL	88TP	88DT	88K <sup>1,2,3</sup>	88L <sup>1,2,4,5,6,7</sup>
<b>Trim description</b>	—	880NL-R	880TP-R	880DT-R	880K-R	373L
<b>Escutcheon plate size</b>	—	3" x 14 <sup>3/16</sup> " x 3 <sup>3/32</sup> "	3" x 14 <sup>3/16</sup> " x 3 <sup>3/32</sup> "	3" x 14 <sup>3/16</sup> " x 3 <sup>3/32</sup> "	3" x 14 <sup>3/16</sup> " x 3 <sup>3/32</sup> "	1 <sup>11/16</sup> " x 7 <sup>1/2</sup> " x 7 <sup>7/8</sup> "
<b>Grip mounting center</b>	—	5 <sup>1/2</sup> "	5 <sup>1/2</sup> "	5 <sup>1/2</sup> "	—	6 <sup>1/4</sup> "
<b>Projection</b>	—	2"	2"	2"	2 <sup>3/4</sup> "	2 <sup>5/8</sup> "
<b>ANSI function</b>	01	03	05	02	08	08/09
<b>Cylinder type</b>	—	Rim	Rim	—	Rim	1 <sup>1/4</sup> " Mortise
<b>Sex bolt quantity #425 (optional)</b>	8	4	4	4	4	4

Optional trims

	NL	TP	DT	K	EO
	<b>Night latch</b> Key retracts latchbolt	Key locks thumbpiece	<b>Dummy trim</b> Pull when dogged	Key locks knob	<b>Exit only</b>
<b>Product description</b>	88NL x 608NL	88TP x 608TP	88DT x 608DT	88K x 606K <sup>1,2,3,5</sup>	88L x 880EO
<b>Trim description</b>	608NL-R	608TP-R	608DT-R	606K-R	880EO-R
<b>Escutcheon plate size</b>	1 <sup>5/8</sup> " x 13 <sup>1/2</sup> " x 3 <sup>1/16</sup> "	1 <sup>5/8</sup> " x 13 <sup>1/2</sup> " x 3 <sup>1/16</sup> "	1 <sup>5/8</sup> " x 13 <sup>1/2</sup> " x 3 <sup>1/16</sup> "	1 <sup>5/8</sup> " x 8 <sup>3/4</sup> " x 3 <sup>1/16</sup> "	3" x 14 <sup>3/16</sup> " x 3 <sup>3/32</sup> "
<b>Grip mounting center</b>	5 <sup>1/2</sup> "	5 <sup>1/2</sup> "	5 <sup>1/2</sup> "	—	—
<b>Projection</b>	2 <sup>1/6</sup> "	2 <sup>1/6</sup> "	2 <sup>1/6</sup> "	2 <sup>3/4</sup> "	—
<b>ANSI function</b>	03	05	02	08	01
<b>Cylinder type</b>	Rim	Rim	—	Rim	—
<b>Sex bolt quantity #425 (optional)</b>	NR	NR	NR	NR	4

<sup>1</sup> If no cylinder operation is required, specify "BE" blank escutcheon, trim always operable: example 88TP-BE.

<sup>2</sup> Matching dummy trim available, use suffix "DT"; example 88K-DT.

<sup>3</sup> Night latch function available, order 88NL x 880K-R rigid.

<sup>4</sup> When using sex bolts, an 889 cover plate is required. See page 24.

<sup>5</sup> When using on wood doors without sex bolts, "WDA" cover plate is required. See page 24.

<sup>6</sup> Not available with E88.

<sup>7</sup> The 373L is shipped L. An NL cylinder plate is also furnished standard (for operation only when key is used).

NR-Not recommended

Notes