

Standard trims

	EO	NL	TP	DT	K	L
	Exit only	Night latch Key retracts latchbolt	Key locks thumbpiece	Dummy trim Pull when dogged	Key locks knob	Key locks lever #06 Standard
Product description	8875EO	8875NL	8875TP ¹	8875DT	8875K ^{1,2}	8875L ^{1,2,3,4,5,6}
Trim description	—	880NL-M	880TP-M	880DT-M	880K-M	373L
Escutcheon plate size	—	3" x 14 ³ / ₁₆ " x 3 ³ / ₃₂ "	3" x 14 ³ / ₁₆ " x 3 ³ / ₃₂ "	3" x 14 ³ / ₁₆ " x 3 ³ / ₃₂ "	3" x 14 ³ / ₁₆ " x 3 ³ / ₃₂ "	1 ¹¹ / ₁₆ " x 7 ¹ / ₂ " x 7 ⁷ / ₈ "
Grip mounting center	—	5 ¹ / ₂ "	5 ¹ / ₂ "	5 ¹ / ₂ "	—	6 ¹ / ₄ "
Projection	—	2"	2"	2"	2 ³ / ₄ "	2 ⁵ / ₈ "
ANSI function	01	03	05	02	08	08/09
Cylinder type	—	1 ¹ / ₄ " Mortise	1 ¹ / ₄ " Mortise	—	1 ¹ / ₄ " Mortise	1 ¹ / ₄ " Mortise
Sex bolt quantity #425 (optional)	8	4	4	4	4	4

Optional trims

	NL	TP	DT	K	EO
	Night latch Key retracts latchbolt	Key locks thumbpiece	Dummy trim Pull when dogged	Key locks knob	Exit only
Product description	8875NL x 608NL	8875TP x 608TP	8875DT x 608DT	8875K x 606K ^{1,2}	8875L x 880EO
Trim description	608NL-M	608TP-M	608DT-M	606K-M	880EO-M
Escutcheon plate size	1 ⁵ / ₈ " x 13 ¹ / ₂ " x 3 ³ / ₁₆ "	1 ⁵ / ₈ " x 13 ¹ / ₂ " x 3 ³ / ₁₆ "	1 ⁵ / ₈ " x 13 ¹ / ₂ " x 3 ³ / ₁₆ "	1 ⁵ / ₈ " x 8 ³ / ₄ " x 3 ³ / ₁₆ "	3" x 14 ³ / ₁₆ " x 3 ³ / ₃₂ "
Grip mounting center	5 ¹ / ₂ "	5 ¹ / ₂ "	5 ¹ / ₂ "	—	—
Projection	2 ¹ / ₆ "	2 ¹ / ₆ "	2 ¹ / ₆ "	2 ³ / ₄ "	—
ANSI function	03	05	02	08	01
Cylinder type	1 ¹ / ₄ " Mortise	1 ¹ / ₄ " Mortise	—	1 ¹ / ₄ " Mortise	—
Sex bolt quantity #425 (optional)	NR	NR	NR	NR	4

¹If no cylinder operation is required, specify "BE" blank escutcheon, trim always operable; example 8875TP-BE.

²Matching dummy trim available, use suffix "DT"; example 8875K-DT.

³When using sex bolts, an 889 cover plate is required. See page 24.

⁴When using on wood doors without sex bolts, "WDA" cover plate is required. See page 24.

⁵The 373L is shipped L. An NL cylinder plate is also furnished standard (for operation only when key is used).

⁶When used with E8875, no cylinder operation is available. Control furnished "BE".

NR-Not recommended

Notes