

**Standard trim**

	EO	DT	NL	NL-OP	TL	TL-BE
<b>Product description</b>	9827EO 9927EO	9827DT 9927DT	9827NL 9927NL	9827NL-OP 9927NL-OP	9827TL 9927TL	9827TL-BE 9927TL-BE
<b>Trim description</b>	—	990DT	990NL-R/V	110NL-MD 110NL-WD	374T X 990DT**	374T-BE X 990DT**
<b>Escutcheon plate size</b>	—	3" x 14 <sup>13/16"</sup> x 3 <sup>3/32"</sup> (76x360x2mm)	3" x 14 <sup>13/16"</sup> x 3 <sup>3/32"</sup> (76x360x2mm)	—	1 <sup>11/16"</sup> x 7 <sup>1/2"</sup> x 7 <sup>7/8"</sup> (43x191x22mm)	1 <sup>11/16"</sup> x 7 <sup>1/2"</sup> x 7 <sup>7/8"</sup> (43x191x22mm)
<b>Pull center to center</b>	—	5 <sup>1/2"</sup> (140mm)	5 <sup>1/2"</sup> (140mm)	—	—	—
<b>Projection</b>	—	2" (51mm)	2" (51mm)	—	3 <sup>1/4"</sup> (83mm)	3 <sup>1/4"</sup> (83mm)
<b>ANSI function</b>	01	02	03	03	11 or 12	16
<b>Cylinder type</b>	—	—	Rim	Rim	1 <sup>1/4"</sup> Mortise	—
<b>Handing</b>	—	—	—	—	—	—
<b>Optional trim</b>	x990EO x996EO	x996K-DT x996L-DT x696DT x697DT	x996K-NL x996L-NL x696NL x697NL			
<b>Optional #425 SNB quantity for device</b>	6	2	2	6	2	2

	L	L-NL	L-BE	L-DT
<b>Product description</b>	9827L 9927L	9827L-NL 9927L-NL	9827L-BE 9927L-BE	9827L-DT 9927L-DT
<b>Trim description</b>	996L-R/V*	996L-NL-R/V	996L-BE-R/V*	996L-DT
<b>Escutcheon plate size</b>	2 <sup>3/4"</sup> x 10 <sup>3/4"</sup> x 2 <sup>7/32"</sup> (70x273x21mm)	2 <sup>3/4"</sup> x 10 <sup>3/4"</sup> x 2 <sup>7/32"</sup> (70x273x21mm)	2 <sup>3/4"</sup> x 10 <sup>3/4"</sup> x 2 <sup>7/32"</sup> (70x273x21mm)	2 <sup>3/4"</sup> x 10 <sup>3/4"</sup> x 2 <sup>7/32"</sup> (70x273x21mm)
<b>Pull center to center</b>	—	—	—	—
<b>Projection</b>	2 <sup>7/8"</sup> (73mm)	2 <sup>7/8"</sup> (73mm)	2 <sup>7/8"</sup> (73mm)	2 <sup>7/8"</sup> (73mm)
<b>ANSI function</b>	08	03	14	02
<b>Cylinder type</b>	Rim	Rim	—	—
<b>Handing</b>	Handed/Reversible	Handed/Reversible	Handed/Reversible	Handed/Reversible
<b>Optional #425 SNB quantity for device</b>	2	2	2	2

\* Electrified lever operation available.

\*\* 377T must be used for WS98/9927 applications.

**Notes**